



OGRN 1025300786610, INN 5321029508

Voliky Novgorod 173012, Russia  
tel.: +7 8162 99 61 09, fax: +7 8162 73 19 40  
email: root@vnov.acron.ru

12, Krasnopresnenskaya Nab., Moscow 123610, Russia  
tel.: +7 495 411 55 94, fax: +7 499 246 23 59  
email: info@acron.ru, www.acron.ru

**ORIGINAL**

TO WHOM IT MAY CONCERN

№ \_\_\_\_\_  
Your ref. \_\_\_\_\_ Date \_\_\_\_\_

### TECHNICAL DATA SHEET

PRODUCT: NP 20-20

We hereby certify that the product meets the following specifications:

|                                                                                                       |                         |
|-------------------------------------------------------------------------------------------------------|-------------------------|
| NITROGEN                                                                                              | 20.0 % MIN, AMONG WHICH |
| IN FORM OF AMMONIUM APPROX.                                                                           | 57 %                    |
| IN FORM OF NITRATE APPROX.                                                                            | 43 %                    |
| PHOSPHORUS (P <sub>2</sub> O <sub>5</sub> ) CITRATE SOLUBLE                                           | 20.0 % MIN              |
| PHOSPHORUS (P <sub>2</sub> O <sub>5</sub> ) WATER SOLUBLE                                             | 15.0 %                  |
| TOTAL PHOSPHORUS (P <sub>2</sub> O <sub>5</sub> )                                                     | 20.0 % MIN              |
| MOISTURE                                                                                              | 1.0 % MAX               |
| GRANULOMETRY:                                                                                         |                         |
| UP TO 1MM                                                                                             | 3 % MAX                 |
| 1-4 MM                                                                                                | 92 % MIN                |
| UP TO 6 MM                                                                                            | 100 %                   |
| STATIC PRILL STRENGTH, MPa (kGf/cm <sup>2</sup> )                                                     | 4 (40)                  |
| FRIABILITY                                                                                            | 100 %                   |
| SAFETY                                                                                                | NON-HAZARDOUS           |
| FREE FLOWING, FREE FROM HARMFUL SUBSTANCES. HAND BREAKABLE LUMPS<br>TO BE CONSIDERED AS FREE FLOWING. |                         |

PJSC ACRON, as manufacturer

Head of Export Department Manager

17.11.2022



A.V. Parfenov